

TAMS INTERTIDAL

Oil Spill Response / Fast Utility / Crew Transfer Vessel



VESSEL SPECIFICATION SHEET



OVERVIEW

Primary Specification	
Registry:	AMSA
Class:	NSCV 2C
Official Number/Unique Identifier:	5248
Length (Overall):	14.2m
Length (Survey):	11.9m
Breadth (Moulded):	4.0m
Design Draft (lightship):	0.3m
Gross Registered Tonnage:	11T
Vessel Weight (lightship):	
Clear Deck Space:	16.5m ²
Cargo Deadweight:	3T
Deck Loading	1T/m ²
Max Passengers	12 + 2
Accommodation:	N/A, (Toilet only)

The data on this specification is published in good faith and for general information purpose only. It does not warrant its accuracy or completeness and to the full extent allowed by law excludes liability.

Machinery	
Propulsion:	2 x 300HP Outboards
Main Engines:	2 x 300HP Suzuki Outboards
Total Propulsion Power:	600HP
Gear Box:	Outboard Drive
Generator:	N/A
Bow Thruster:	N/A

Operational Performance	
Full Operating Speed:	28 Knots
Economic Operating Speed/consumption:	20 Knots / 100L/Hr
Consumption at Idle:	



OVERVIEW

Tank capacities	
Fuel:	550Lt (2 x 275Lt tanks)
Fresh Water:	300Lt (2 x 150Lt tanks)
Water Ballast:	N/A
Lube Oil:	N/A
Waste Oil:	N/A
Sullage:	N/A
Fuel Transfer Pump:	N/A
Bilge & Ballast Pump:	Yes
Fire Pump:	N/A

Deck Machinery	
Tow Winch:	N/A
Tugger Winch:	N/A
Anchor Windlass:	1 x Electric Anchor Winch 1 x manual winch
Capstan:	750kg electric (optional)
Stern Roller	N/A
Deck Crane (Davit)	300kg crane (optional)
Transfer Locations	Port, Bow & Stern
Misc Equipment	

Navigational/Communications	
Radar System:	N/A
Depth Sounder:	Simrad
HF Radio:	N/A
VHF Radio:	Yes
Call Sign:	
Compass:	Yes
GPS:	Simrad
Chart Plotter:	Simrad
Auto Pilot:	N/A
AIS:	
MMSI:	



The data on this specification is published in good faith and for general information purpose only. It does not warrant its accuracy or completeness and to the full extent allowed by law excludes liability.