



## OVERVIEW

Primary Specification	
<b>Type of vessel</b>	Crew boat/general purpose
<b>In survey to</b>	USL/NSCV 2C
<b>Home Port</b>	Gladstone / Queensland
<b>Operator:</b>	Total AMS Pty Ltd
<b>Builder:</b>	Subsea
<b>Construction Material:</b>	Aluminium
<b>Length (Overall):</b>	9m
<b>Beam</b>	3m
<b>Depth</b>	0.7m
<b>Draft</b>	0.5m (lightship)
<b>Displacement</b>	6T
<b>Safety Equipment:</b>	To USL/NSCV requirements
<b>Life rafts:</b>	1 X 16 person RFD
<b>Features:</b>	Bow access stairs, 2 x transom doors, 2 x bulwark doors
<b>Radio:</b>	GME
<b>Free Deck area:</b>	7m <sup>2</sup>

Machinery	
<b>Engines:</b>	2 x 101kw Honda outboard
<b>Propellers</b>	4 blade Solas Stainless steel
<b>Steering system</b>	Hydrive hydraulic
<b>Operational Performance</b>	
<b>Maximum speed</b>	29 knots light ship
<b>Cruising speed</b>	25 Knots
<b>Range</b>	80 nm @ 20 Knots
<b>Fuel Capacity:</b>	200L

The data on this specification is published in good faith and for general information purpose only. It does not warrant its accuracy or completeness and to the full extent allowed by law excludes liability.